

baufan®

Special Paint for bathtub

Technical information sheet

1 Set / Item no.025701000 / EAN 4007954257012



2-component coating system for long-lasting surface renovation. Ideal for bathtubs, shower trays and washbasins made of enamelled steel as well as for wall tiles and plastic kitchen fronts. Provides a highly durable, smooth surface with a new, fresh look - perfect for quick bathroom and kitchen renovation without replacement.

- Top coat and sealer in one step
- glossy finish
- Extremely durable and easy to clean
- Solvent-free and mild odour
- white opaque
- Varnish and hardener for approx. 2.8 m²

Area of application

2-component lacquer system for bathtubs, shower trays, washbasins, wall tiles and kitchen fronts made of plastic - high-gloss, extremely durable.

Preparation

The substrate must be dry, clean and free of dust and grease. Remove all soap residues, dirt, limescale and silicone residues - e.g. with leaching agent and degreaser or silicone remover. Roughen the entire surface with sandpaper (1st sanding pass with P120 grit, 2nd sanding pass with P320 grit) and remove all sanding dust. Mask off surfaces that are not to be coated. The substrate temperature should be +22 to +25 °C.

Processing

Store the paint components at a temperature of +22 °C for at least 24 hours before use. Pour the contents of the hardener bottle completely into the paint can, stir the mixture thoroughly for at least 2 minutes with a stirring stick and pour into a paint tray. Process the mixed paint within 50 minutes. Pre-coat hard-to-reach areas - such as curves and edges - with a brush. Quickly apply the paint to the surface with a brush and roughly blend. Immediately spread the paint with a roller in a longitudinal and transverse direction, rolling it out thinly and evenly to avoid the formation of runs and drips. Finally, roll the surface with the roller in one direction to achieve the most even surface possible. The coating is dust-resistant after approx. 5 hours. For the next five days, keep the room temperature constant and avoid exposure to water. Tinting: For coloured coatings on tiles or kitchen fronts, the paint can be tinted with the specified universal tinting concentrates. Do not tint the paint for coating bathtubs and shower trays.

Consumption

The content is sufficient for approx. 2.8 m².

Storage

Keep container tightly closed and store in a cool, frost-free place out of the reach of children.

Notes

Clean tools with water immediately after use. The coated surface can be cleaned with standard mild household cleaners (do not use abrasive cleaners). Not suitable for coating floor tiles, acrylic bathtubs and worktops. Substrates with special dirt-repellent properties (e.g. lotus effect) are not suitable for subsequent coating. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues according to waste code no. EWC 08 01 12. Tools and accessories required (not included in the package): Sandpaper in two grit sizes (P120 and P320), dust binding cloth, stirring pad, paint tray, solvent-resistant professional flat brush, solvent-resistant professional paint roller, leaching agent and degreaser, silicone remover.

Status: 07.09.2026

Page 1/1

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.