Decor and Plaster Primer

Technical information sheet

8kg / Item no.013168 / EAN 4016215013168
16kg / Item no.026203008 / EAN 4016215013175



The decorative and plaster primer is an adhesion-promoting special primer for mineral, silicate and synthetic resin coatings. The finely textured, white pigmented decorative primer ensures even surfaces, good coverage and optimum adhesion. Diffusible, solvent-free and suitable for interior and exterior use - the perfect basis for high-quality top coats.

- Adhesion-promoting special primer for subsequent coatings with mineral, silicate and synthetic resin plasters
- Substrate coating for painting techniques with glazes and emulsion paints
- Texturising coating for interior use
- white pigmented - good coverage
- Highly water vapour permeable
- Free from preservatives, solvents and plasticisers
- for indoors and outdoors

Area of application

Special primer for absorbent substrates, improves adhesion and creates a fine structure for fine plasters as well as interior and exterior wall paints.

Preparation

For substrates such as concrete, cement and lime-cement plaster, masonry, gypsum substrates, fibre cement boards and absorbent dispersion-bonded plasters as well as paint coats. The substrate must be dry, clean, sound and free of dust and grease. Remove loose material, old wallpaper and poorly adhering coats of paint from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Repair cracks, holes and unevenness with a suitable baufan levelling compound.

Processing

Stir well before use and apply with a roller, brush or paintbrush. If necessary, dilute with max. 5 % Silicate Fixative. Ensure even coverage so that no colour differences in the substrate become visible. Clean tools with water immediately after use. Surfaces already painted with baufan Dekor- und Putzgrund must not be filled with gypsum-based levelling compounds. We recommend baufan Allesspachtel for this purpose. Drying time: approx. 8 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time in unfavourable conditions. Tinting: With max. 5% universal tinting concentrates (LW-Oxyd-Ty pen). We recommend matching the colour of the primer to the subsequent product.

Consumption

Smooth surfaces/fine plaster grain → from 350 g/m² Determine exact consumption quantity by test coating on the object.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Avoid eating, drinking and smoking while using the paint. Wear safety goggles (not glass). In case of contact with eyes or skin,

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling. GISCODE for coating materials: BSW10 EU VOC limit value for this product: (Cat.: A/h, Wb) = 30 g/l (2010) VOC content of this product max.: 15 g/l

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.