LF 712 Primer

Technical information sheet

/ Item no.006402208 / EAN 4016215105139
/ Item no.006403208 / EAN 4016215105146



Solvent-free acrylate primer for interior and exterior use, designed to stabilise sandy and chalky substrates and reduce absorbency. High penetration depth thanks to ultra-fine hydrosol acrylate.

- Hydrosol acrylate
- stabilises the substrate and regulates its absorbency
- can be diluted with water up to a ratio of 1:1
- free from solvents and plasticisers
- high penetration depth
- for indoors and outdoors

Area of application

A primer for stabilising sandy and chalky substrates and for reducing absorbency in both indoor and outdoor applications.

Preparation

Suitable for use on all dry mineral substrates (such as concrete, gypsum, lime and cement plaster), plasterboard, gypsum fibreboard, cement fibreboard and similar drywall panels. Cover any areas not to be treated before priming, as dried splashes are difficult to remove later on.

Processing

Apply profimur Deep Primer LF using a paintbrush, brush or a suitable sprayer. To adjust the absorbency, the Deep Primer LF can be diluted with water in a ratio of up to 1:1.

Consumption

1 litre covers approx. 10 m² with a single coat.

Storage

Keep container tightly closed, childproof and store in a cool but frost-free place.

Notes

Do not apply when the surface and ambient temperatures are below +5 °C. Clean tools with water immediately after use.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website at www.baufan.de or at info@baufan.de.

Only send completely empty containers for recycling. Dried-out material residues can be disposed of as household waste or as construction site waste. Dispose of liquid residues in accordance with EWC waste code 08 01 12. Do not allow the product to enter the sewer system, watercourses or the ground.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.