Wallpaper Adhesive – Special

Technical information sheet

200g / Item no.530310 / EAN 4002175029011



This inexpensive wallpaper paste in tested quality is ideal for woodchip wallpaper as well as heavy and dry removable wallpaper. It is easy to mix, offers reliable adhesive strength and enables clean, even application. For a secure hold and impressive results in classic wall design.

- Reinforced with synthetic resin
- ready for use in approx. 30 minutes

Area of application

Wallpaper paste for gluing heavy wallpaper and woodchip.

Preparation

Only wallpaper on a dry, stable, clean, smooth and firm substrate. Remove wallpaper residue, distemper and loose paint. Repair cracks, holes and unevenness with filler. Prime sanding and chalking substrates with Deep Primer LF. Pre-paste (table) or prime highly absorbent substrates. Pretreat coarse-grained plaster with a maculate.

Processing

Paste the wallpaper strips evenly and generously, lay them together and, after observing the prescribed soaking time, apply them butt-jointed. It is essential to follow the wallpaper manufacturer's instructions. For slightly absorbent substrates and to increase moisture resistance, we recommend adding one 750 g can of wallcovering adhesive per pack of special paste.

Mixing ratio: Pre-pasting: mix 1:40 = 8 litres of water = 60-80 m² heavy wallpapers: mix 1:20 = 4 litres of water = 22-26 m² (4-5 rolls) woodchip wallpaper: mix 1:20 = 4 litres of water = 22-26 m² special bondings, unprinted embossed wallpapers: mix 1:15 = 3 litres of water = 10-15 m²

Storage

Keep container tightly closed, dry and cool, but frost-free. Keep out of the reach of children.

Notes

Do not use below +5 °C. Remove paste residues immediately with a damp cloth. Clean tools with water after use. Free from isothiazolinones, so the mixed paste should be used soon. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues according to waste code no. EWC 08 04 10.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.